

				
Modelo	ZEBRA NX7500	ARUBA 7210	HUAWEI AC6605	CISCO 5760
APs Suportados	2k	512	1.024	1k
Max. Users / Devices	65k	16k	10k	12k
Scalability	Licenses for 8, 64, 256 or 1024	x	Licenses for 8, 16, 64 or 128 APs	25, 50, 100, 250, 500 e 1000
WLANs	256	x	16k	512
Porta 10/100/1000	6	2	24	1
Giga Ethernet (GBIC/SFP)	X	4 SPF+	2 SPF+	6 SPF+
Max. VLANs	1k	4k	4k	512
PoE	No	No	Yes	No
Porta Console	Yes	Yes	Yes	Yes
Data Throughput	20 Gbps	20 Gbps	40 Gbps	60 Gbps
Redundante Power Supply	Yes	Yes	Yes	Yes
Height	430 x 44.2 x 320.7 mm	4.4 x 44.5 x 44.5 cm	43.6 x 44.2 x 420 mm	4.45 x 44.5 x 45 cm
Weight	4.5 kg	7.45 kg (with one AC power)	5.48 kg	8.9 kg
Form Factor	1U	1U	1U	1U
Operating Temperature	32°F to 104°F / 0°C to 40°C	0° C to 40° C	0° C to 45° C	23°F to 113°F / -5°C to 45°C
Operating Humidity	5% to 85% (non-condensing)	5% to 95%	5% to 95%	5% to 95% (non-condensing)
USB ports	2	1	1 (mini)	2
Preço	Clique Aqui	Clique Aqui	Clique Aqui	Clique Aqui