

				
Modelo	ZEBRA NX5500	ARUBA 7024	HUAWEI AC6005	CISCO 5500
APs Suportados	512	32	256	500
Scalability	16, 64 e 128	X	X	12, 25, 50, 100, 250 e 500
Max. Users / Devices	16k	2k	2k	7k
WLANs	256	X	16k	512
Porta 10/100/1000	6	24	8	8
Max. VLANs	256	4k	4k	512
PoE	No	Yes	Yes	No
Porta Console	Yes	Yes	Yes	Yes
Data Throughput	6 Gbps	4 Gbps	4 Gbps	8 Gbps
Redundante Power Supply	No	No	No	Yes
Height	1.75 in x 12 in x 10 in	4.37 x 44.2 x 31.3 cm	43.6 x 320 x 233.6 mm	440 x 539 x 44.5 mm
Weight	2.15 kg	1.0 kg	2.9 kg	9.1 kg
Form Factor	1U	1U	1U	1U
Operating Temperature	32°F to 104°F / 0°C to 40°C	0° C to 40° C	-5° C to 50° C	32°F to 104°F / 0°C to 40°C
Operating Humidity	5% to 85% (non-condensing)	10% to 95%	5% to 95%	10% to 95%
USB ports	2	1	1	1 (mini)
Preço	Clique Aqui	Clique Aqui	Clique Aqui	Clique Aqui